

# CAURUS

Hybrid system with building mass connection



## QUICK FACTS

- In combination with A11-S, SPECTRA M-S, VARICOOL TKM
- Very high heating & cooling capacity
- Active area ratio: 85 %
- Superior sound absorption values (class A)
- Building mass connection
- Integrated cross-talk sound attenuation (option)
- Low structural height
- Sound power level  $L_w$ : < 30 dB (A)
- Fresh air intake is silent and draught-free



# Technical description

## General

Thanks to its comprehensive functionality, the hybrid system CAURUS plus the A11-S or SPECTRA M-S heating & cooling sails achieves an optimum room climate in any environment. It has very high cooling and heating capacities, a comfortable air supply and superior acoustic properties. According to the principle of the thermoactive component system, it also includes the storage mass for the dissipation of heat loads in the overall room thermal concept. This reduces energy requirements and operating costs.

## Activation

**Water system:** The radiant ceiling is a passive system that in the case of cooling absorbs heat from the room via the ceiling surface, transfers it to the water, which is conducted in activation registers, and dissipates it, respectively emits heat in the case of heating.

Two variants of activation registers are available for activating the radiant metal ceiling system:

### Activation register A11-S

- Copper pipe meanders welded to aluminum heat-conducting rails.
- Connected to the ceiling panel using adhesive technology.

### Activation register SPECTRA M-S

- Copper pipe meanders pressed into aluminum heat-conducting profile with magnetic tape.
- Connected to the ceiling panel using magnet technology. Advantages: The registers can be supplied, fixed and hydraulically connected independently of the ceiling panels. These can be assembled at the end of the installation work. This reduces construction time and the risk of contamination.

## Optional performance plus: Convector Wings

When using the activation register A11, a further increase in performance can be achieved by using the Convector Wings developed by Barcol-Air.



Convector Wings are matt black anodized aluminum profiles with slotted «wings» on both sides. With the profile that opens downwards, the Convector Wings can be attached to the straight sections of a pipe meander. This multiplies the heat exchange surface of the radiant ceiling sail, which leads to an increase in water capacity.

## Functions

In addition to the thermal functions of cooling/heating and the active concrete management, there is the possibility of further integration: acoustically effective inserts or baffles (ARCHISONIC®), various built-in components (e.g. smoke detectors, lighting).

## Combination

- CAURUS + A11-S + ARCHISONIC®
- CAURUS + SPECTRA M-S
- CAURUS + VARICOOL TKM



Optional performance plus: Convector Wings

## Functional description nozzle channel

With supply air quantities of up to  $35 \text{ m}^3/\text{h} \cdot \text{lm}$  per sail, the supply air is introduced horizontally into the room on one side of the sail above the ceiling panels. The warm room air is drawn in by specially developed high-performance induction nozzles on the opposite side of the sail, accelerated above the supply air channel and thereby achieved a high energy transfer into the concrete. The temporarily stored energy can be dissipated at night – if possible with free cooling. Due to the high ventilation efficiency in the room, a draft-free and complete room mixing with a homogeneous temperature profile is created within a very short time.

## Operation

### Day

The hygienically necessary air volume flow emerges from the high-performance induction nozzles. This induces warm room air from behind the sail. Part of the energy is dissipated directly, another heats the concrete. The room temperature always remains comfortable.

### Night

At night, no supply air is required in the building. The water can be cooled by free cooling (without the use of the refrigerator). Through the exchange of radiation between warm concrete and cold heat conducting rails, the energy is extracted from the concrete and prepared for the absorption of excess energy the next day.



## Supply air volume flow

Maximum supply air volume flow per linear meter of nozzle channel at under temperature:

6 K	$35 \text{ m}^3/\text{h}$
8 K	$33 \text{ m}^3/\text{h}$
10 K	$30 \text{ m}^3/\text{h}$

## CAURUS as a bass absorber

The CAURUS can also be optionally designed as a bass absorber. For this purpose, the air duct is fitted with special internal insulation. The low-frequency absorber particularly shows its strengths in the frequency ranges of 100 Hz - 250 Hz.



# Technical data

## Capacity


### Water

Initial data is presented below.


Material ceiling panel	Aluminium	Steel
Perforation	Rg 1,5 – 11 %	Rg 1,5 – 11 %
Activation (Distance heat conducting rails hcr: 100 mm)	A11 ---- ②	A11 + Convector Wings ..... ① A11 ——— ③ Spectra M - - - - ④
Activation method	on fleece	on fleece

(Capacity specifications without object-specific performance-increasing factors. Depending on the configuration, an additional output of 20 w/m<sup>2</sup> of panel area is achieved through concrete management.)

EN 14240:2004



EN 14037:2016



Activation	Version	Cooling 8 K	Cooling 10 K	Heating 15 K <sup>(1)</sup>
A11-S	① Steel + Convector Wings	up to 140 w/m <sup>2</sup>	up to 179 w/m <sup>2</sup>	up to 117 w/m <sup>2</sup> (---)
A11-S	② Aluminium	up to 125 w/m <sup>2</sup>	up to 162 w/m <sup>2</sup>	up to 117 w/m <sup>2</sup> (---)
A11-S	③ Steel	up to 120 w/m <sup>2</sup>	up to 153 w/m <sup>2</sup>	up to 112 w/m <sup>2</sup>
Spectra M-S	④ Steel	up to 110 w/m <sup>2</sup>	up to 140 w/m <sup>2</sup>	up to 102 w/m <sup>2</sup>

<sup>1)</sup> When the supply air is running, there is a 20 to 40 % higher heating capacity.

### Notice

- SN EN 14240: The cooling capacity is related to the active area according to SN EN 14240:2004. The active area is calculated according to SN EN 14240 from the number of heat-conducting rails x length of heat conducting rail x distance between heat-conducting rails.
- SN EN 14037: The heating capacity is related to the active area according to SN EN 14037:2016. The active area is calculated according to SN EN 14037 from the length of the ceiling panel x the width of the ceiling panel.

## Air

Air volume	2 K	4 K	6 K	8 K	10 K
50 m <sup>3</sup> /h	32 W	64 W	96 W	128 W	160 W
75 m <sup>3</sup> /h	48 W	96 W	145 W	192 W	240 W
100 m <sup>3</sup> /h	64 W	128 W	192 W	256 W	320 W
200 m <sup>3</sup> /h	128 W	256 W	384 W	512 W	640 W

Base:  $\rho_L = 1,15 \text{ kg/m}^3$  /  $c_L = 1,006 \text{ kJ/kgK}$

Recommended use for EN ISO 7730, class A / B. Further uses possible according to project-specific evaluation.




## Acoustics

### Sound absorption (Ceiling panel)

Initial data: Radiant metal ceiling sail perforated, distance hcr 100 mm, installation height 200 mm.

With the supply air channel, the total sound absorption level elevated  $\alpha_w$  by 0,05.




Perforation 1,5 mm – 11 %, with acoustic fleece

Additional inlay	without	1 strip on the long sides of cp	Strips between hcr
Practical sound absorption $\alpha_p$	250: 0,55 500: 0,90 1k: 0,75 2k: 0,75 4k: 0,65	250: 0,70 500: 1,00 1k: 0,95 2k: 0,90 4k: 0,75	250: 0,95 500: 1,00 1k: 1,00 2k: 0,90 4k: 0,80
sound absorption $\alpha_{pw}$	$\alpha_w$ : 0,75	$\alpha_w$ : 0,90	$\alpha_w$ : 0,95
Sound absorption class	C	A	A

### Depth absorber

Initial data: Perforated metal heating/cooling sails, distance hcr 100 mm, installation height 200 mm.

With bass absorber integrated in CAURUS hybrid system.



Perforation 1,5 mm – 11 %, with acoustic fleece

Additional inlay	Strips between hcr
Practical sound absorption $\alpha_p$	125: 0,50 250: 0,95 500: 1,00 1k: 1,00 2k: 0,95 4k: 0,80
sound absorption $\alpha_{pw}$	$\alpha_w$ : 0,95
Sound absorption class	A

## Air connection box

### Standard sound level difference (Telephony sound attenuation)

Versions	only supply air	combination supply and exhaust air
without internal attenuation	$D_{n,e,w} = 58 \text{ dB}$	$D_{n,e,w} = 50 \text{ dB}$
with internal attenuation	$D_{n,e,w} = 62 \text{ dB}$	$D_{n,e,w} = 55 \text{ dB}$

### Sound power level $L_{WA}$

Supply air volume	$q_v$ $q_v/\text{lm channel}$	$\text{m}^3/\text{h}$ $\text{m}^3/\text{lm} \cdot \text{h}$	76 25	90 30	104 35	118 40	136 45
Sound power level	$L_{WA}$	dB	24,1	27,3	31,0	34,7	38,2

# System

## Ceiling system

- Sail
  - Rectangular panels

## System components

- Nozzle channel with induction nozzles
- Air connection box for access in the corridor

## Installation systems

- Installation high: 80 – 200 mm
  - Hook-on systems
  - Threaded rods or ropes

# Materials, weight and dimensions

## Materials and weight

Activation	Material	Weight (incl. activation, water)	Building material class <sup>(1)</sup> (EN 13501-1)
A11	Aluminium 1,00 mm	3,8 – 6,5 kg/m <sup>2</sup>	A2-s1, d0
A11	Steel 0,70 mm	6,5 – 9,0 kg/m <sup>2</sup>	A2-s1, d0
Spectra M	Steel 0,70 mm	10,0 – 13,3 kg/m <sup>2</sup>	B-s2, d0

<sup>1)</sup> Also depends on the acoustic inserts.

## Dimensions

Sail length	Sail width	Sail height
min. 800 mm	min. 400 mm	min. 30 mm <sup>(1)</sup>
project specific	max. 1200 mm	max. 50 mm

<sup>1)</sup> System structure without tolerance of the concrete ceiling.

## Changing nozzles

If you want to be able to easily replace nozzles at a later time (e.g. for blind nozzles), the upper edge of the channel must be away 20 mm from the concrete ceiling. The nozzles can be used from above without screws. Alternatively (if no 20 mm above the channel is possible) they can be inserted into the channel from below (ATTENTION: the direction of the nozzle discharge changes! The nozzles must be screwed!). With nozzles from below it should be noted that the nozzles still blow out OVER the panel edge (loss of capacity).



80 mm installation height <sup>(1)</sup>  
 40 mm perforated metal ceiling panel  
 10 mm substructure  
 25 mm supply air channel  
 5 mm air gap

## Surface

### Versions

- Powder coating
- Digital printing on request

### Colors


- Standard RAL 9010
- Other RAL / NCS colors on request

### Perforations


- Standard perforations
- Other perforations on request

Standard perforations:


Rd 1,5 – 11 %




Rg 1,5 – 11 %



Rd 1,5 – 22 %



Rg 2,5 – 16 %



## International

### Barcol-Air Group AG

Wiesenstrasse 5  
8603 Schwerzenbach  
T +41 58 219 40 00  
F +41 58 218 40 01  
info@barcolair.com

## Switzerland



### Barcol-Air AG

Wiesenstrasse 5  
8603 Schwerzenbach  
T +41 58 219 40 00  
F +41 58 218 40 01  
info@barcolair.com

### Barcol-Air AG

Via Bagutti 14  
6900 Lugano  
T +41 58 219 45 00  
F +41 58 219 45 01  
ticino@barcolair.com

## Germany

### Swegon Klimadecken GmbH

Schwarzwaldstrasse 2  
64646 Heppenheim  
T +49 6252 7907-0  
F +49 6252 7907-31  
vertrieb.klimadecken@swegon.de  
swegon.de/klimadecken

## France

### Barcol-Air France SAS

Parc Saint Christophe  
10, avenue de l'Entreprise  
95861 Cergy-Pontoise Cedex  
T +33 134 24 35 26  
F +33 134 24 35 21  
france@barcolair.com

## Italy

### Barcol-Air Italia S.r.l.

Via Leone XIII n. 14  
20145 Milano  
T +41 58 219 45 40  
F +41 58 219 45 01  
italia@barcolair.com